







Its main advantage is the possibility to use a quick coupling system without losing breakout force at the bucket. Available in mechanical and hydraulic version it enables quick tool switch and safeguards excavator's digging force, a vital characteristic for many earthmoving tasks.

- The only quick coupler that doesn't mean loss of breakout force.
- The patented design allows quick **attachment interchange** while keeping the original geometry of the excavator arm unchanged.
- The main frame is casted to ensure **maximum safety and durability**.
- A **double locking system** in the back prevents attachment movements in any direction.
- **Adapters** are available for buckets, hammers and many other attachments.hydraulic attachment.







TECHNICAL DATA BT.QQ

RIF. 97890/E 12/18 REV.02	MODEL		QC10M	QC20M	Q C31М	QC41M	QC45M	QC10H	QC20H	QC31H	QC41H	QC45H	QC50H	QC60H
			MECHANICAL					HYDRAULIC						
	EXCAVATOR WEIGHT	t	5-8	9-14	15-24	25-30	30-40	5-8	9-14	15-24	25-30	30-40	40-60	60-70
	QUICK COUPLER WEIGHT	kg	120	200	280	400	550	120	200	280	400	550	850	1400

We are constantly improving our products and therefore we reserve the right to change the design and technical specifications without prior notice.



